


Coil pack quantity and dimensions

Coil pack quantity




Puriton® pipe

Pipe nominal diameter	Pack quantity	Total pack length	Pack quantity	Total pack length	Pack quantity	Total pack length
mm	25 m	m	50 m	m	100 m	m
25	-	-	6	300	-	-
32	-	-	6	300	-	-
63	6	150	6	300	4	400

SC80 and universal black PE100


Pipe nominal diameter	Pack quantity	Total pack length	Pack quantity	Total pack length	Pack quantity	Total pack length	Pack quantity	Total pack length
mm	25 m	m	50 m	m	100 m	m	150 m	m
20	9	225	9	450	9	900	7	1050
25	10	250	8	400	7	700	5	750
32	8	200	8	400	4	400	4	600
40	-	-	-	-	6	600	5	750
50	9	225	5	250	5	500	4	600
63	9	225	6	300	4	400	3	450

Coil dimensions



Puriton® pipe

Pipe nominal diameter	SDR	Coil length	Coil outer diameter	Coil inner diameter	Coil width	Coil banding sequence	Coil weight
mm		m	mm	mm	mm		kg
25	11	50	965	785	175	-	14.5
32	11	50	1015	785	175	-	22.0
63	11	25	1510	1275	230	•	36.3
63	11	50	1815	1275	208	•	72.5
63	11	100	1815	1275	310	•	145.0
90	11	50	2220	1800	320	•	137.9
90	11	100	2440	1800	410	•	275.7
90	17	50	2930	2500	320	•	102.7
90	17	100	3000	2500	410	•	205.4
110	11	50	3000	2500	320	•	197.1
110	11	100	3200	2500	410	•	394.1
110	17	50	3000	2500	400	•	145.7
110	17	100	3200	2500	500	•	291.4
125	11	50	3000	2500	450	•	251.0
125	11	100	3200	2500	600	•	502.0
125	17	50	3000	2500	450	•	181.6
125	17	100	3200	2500	600	•	363.1
160	11	50	3590	3000	530	•	397.6
160	11	100	3850	3000	700	•	795.2
160	17	50	3590	3000	530	•	284.4
160	17	100	3850	3000	700	•	568.8
180	11	50	3800	3000	630	•	496.3
180	11	100	4000	3000	800	•	992.6
180	17	50	3800	3000	630	•	353.0
180	17	100	4000	3000	800	•	706.0



SC80, SC100, universal black PE100 and ProFuse® coil dimensions

Pipe nominal diameter	SDR	Coil length	Coil outer diameter	Coil inner diameter	Coil width	Coil banding sequence	Coil weight SC80 pipe	Coil weight SC100 PE100 pipe	Coil weight ProFuse® pipe
mm		m	mm	mm	mm		kg	kg	kg
20	9	25	710	600	100	-	3.5	3.5	-
20	9	50	780	600	100	-	7.0	7.0	-
20	9	100	885	600	120	-	14.0	14.0	-
20	9	150	885	600	180	-	21.0	21.0	-
25	11	25	740	600	150	-	4.5	4.5	-
25	11	50	780	600	150	-	9.0	9.0	-
25	11	100	910	600	175	-	18.0	18.0	-
25	11	150	910	600	225	-	27.0	27.0	-
32	11	25	875	700	145	-	7.3	7.5	-
32	11	50	990	700	145	-	14.5	15.0	-
32	11	100	990	700	275	-	29.0	30.0	-
32	11	150	1100	700	275	-	43.5	45.0	-
40	11	100	1800	1275	170	-	45.0	-	-
40	11	150	1780	1275	220	-	67.5	-	-
50	11	25	1600	1275	160	•	17.5	17.8	-
50	11	50	1800	1275	220	•	35.0	35.6	-
50	11	100	1880	1275	210	•	70.0	71.2	-
50	11	150	1880	1275	270	•	105.0	106.8	-
63	11	25	1740	1275	130	•	27.5	28.0	-
63	11	50	1815	1275	195	•	55.0	56.0	-
63	11	100	1810	1275	300	•	110.0	112.0	-
63	11	150	2035	1275	345	•	165.0	168.0	-
75	17	50	2220	1800	255	•	-	-	70.0
75	17	100	2220	1800	350	•	-	-	140.0
90	11	50	2220	1800	320	•	-	113.0	135.0
90	11	100	2440	1800	410	•	-	226.0	270.0
90	17	50	2930	2500	320	•	-	77.5	100.0
90	17	100	3000	2500	410	•	-	145.0	200.0
110	11	50	3000	2500	400	•	-	166.5	190.0
110	11	100	3200	2500	500	•	-	333.0	380.0
110	17	50	3000	2500	400	•	-	115.5	140.0
110	17	100	3200	2500	550	•	-	131.0	280.0
125	11	50	3000	2500	450	•	-	216.5	245.0
125	11	100	3200	2500	600	•	-	433.0	490.0
125	17	50	3000	2500	450	•	-	147.0	175.0
125	17	100	3200	2500	600	•	-	294.0	350.0
140	17	50	3530	3000	420	•	-	-	215.0
140	17	100	3700	3000	690	•	-	-	430.0
160	11	50	3590	3000	530	•	-	354.0	385.0
160	11	100	3850	3000	700	•	-	708.0	870.0
160	17	50	3590	3000	530	•	-	241.0	275.0
160	17	100	3850	3000	700	•	-	482.0	550.0
180	11	50	3800	3000	630	•	-	447.0	485.0
180	11	100	4000	3000	800	•	-	894.0	970.0
180	17	50	3800	3000	630	•	-	304.0	340.0
180	17	100	4000	3000	800	•	-	608.0	780.0

Note: The coil banding sequence can be found within this brochure. As part of Radius Systems' commitment to ongoing product development, pipe coil dimensions may be subject to change.