


# Product Range



## Tapping tees - 32 mm outlet

Our range of tapping tees have been specifically designed with a universal integral cutter and NBR O-ring seal, approved for use in gas and water applications. Manufactured from high performance PE100 our tapping tees are designed with a Unifit™ base to suit a range of pipe diameters, considerably reducing the need to carry additional stock of fittings. Quick and easy to install, our tapping tees are available with a 32 or 63 mm outlet, in diameters 40 mm to 560 mm.



Nominal diameter mm	Pack qty	Dimensions mm							Max weight kg	Fuse time sec	Cool time min	Product code 40 V 4.0 mm pin
		ØB	H	HC	HS	L	ØS	W				
40 <sup>5</sup>	5	20	151	120	71	115	32	62	0.3	40	4	WA6333
55	5	20	136	110	71	115	32	67	0.3	55	4	WA6335
63 & 2"	5	20	141	110	71	115	32	77	0.3	55	4	WA6332
75	5	20	129	110	71	115	32	75	0.3	55	4	WA6337
90 & 3"	5	20	130	111	71	115	32	90	0.3	55	4	WA6331
110 - 140 & 4"	5	20	128	115	71	115	32	83	0.3	55	4	WA6330
140 - 180 & 6"	5	20	125	115	71	115	32	88	0.3	55	4	WA6342
200 - 250 & 8" <sup>6</sup>	5	20	122	115	71	115	32	90	0.3	55	4	WA6348
268 - 355 <sup>6</sup>	5	20	120	115	71	115	32	90	0.3	55	4	WA6359
400 - 560 <sup>6,7,8</sup>	5	20	118	115	71	115	32	90	0.3	60	4	WA6363



## Tapping tees - 63 mm outlet

Nominal diameter mm	Pack qty	Dimensions mm							Max weight kg	Fuse time sec	Cool time min	Product code 40 V 4.0 mm pin
		ØB	H	HC	HS	L	ØS	W				
63 & 2"	5	34	170	135	106	170	63	77	0.76	55	4	WA6460
75	5	34	166	143	106	170	63	100	0.76	55	4	WA6462
90 & 3"	5	34	166	135	106	170	63	100	0.76	60	4	WA6463
110 - 125 & 4"	5	34	162	137	106	170	63	105	0.76	70	4	WA6466
140 - 155	5	34	152	137	106	170	63	110	0.76	70	4	WA6467
155 - 180 & 6"	5	34	152	135	106	170	63	110	0.76	70	4	WA6471
200 <sup>6</sup>	5	34	146	135	106	170	63	110	0.76	70	4	WA6472
213 - 280 & 8" <sup>6</sup>	5	34	146	135	106	170	63	110	0.76	75	5	WA6476
315 - 355 <sup>6</sup>	5	34	144	135	106	170	63	110	0.76	80	4	WA6482
400 - 469 <sup>6,8</sup>	5	34	142	135	106	170	63	110	0.76	75	4	WA6486
500 - 560 <sup>6,8</sup>	5	34	139	135	106	170	63	110	0.76	80	5	WA6492

### Note:

- 5- Fitted with an under-part
  - 6- Fitted with a thread follower which must be removed after tapping the main. See guidance within this brochure
  - 7- Not suitable for use with 560mm SDR17 and SDR17.6 pipe
  - 8- Not suitable for use with SDR11 pipe
- ØB = cut hole diameter

For pipe connections identified in footnotes 7 and 8, please contact Radius Subterra our live pipeline engineering division on t: 01773 582317 or e: radius.subterra@radius-systems.com.

For the MOP of tapping tee products for gas applications, please refer to the packaging label

For instructions on how to install our tapping tees, please refer to the jointing guidance within this brochure.

Always refer to the fitting and packaging label for the most up to date information.